

GO! Flex - Technical Table

Capacity		Speed (m/s)	Car dimensions (mm) Height 2100 mm		Shaft dimensions (mm)				Clearance (mm)
People	Load (Kg)		Width	Depth	Width	Depth	Pit	Headroom	
6	480	1,0/1,6	1000	1250	1500	1500/1600	1025/1155	3400/3600	800
8	630	1,0/1,6	1100	1400	1600	1650	1025/1155	3400/3600	900
10	800	1,0/1,6	1200	1500	1700/1750	1750	1025/1300	3400/3650	900
13	1000	1,0/1,6	1100	2100	1600/1650	2350	1025/1400	3400/3650	900
13	1000	1,0/1,6	1100	2100	1750	2350	1025/1400	3750	1000
15	1125	1,0/1,6	1200	2150	1700/1750	2400	1025/1400	3400/3650	1000
6	480	1,0/1,6	1000	1250	1600	1585/1600	1025/1155	3400/3600	800
8	630	1,0/1,6	1100	1400	1800	1650	1025/1155	3750	900
10	800	1,0/1,6	1200	1500	1950	1750	1025/1300	3400/3650	900
13	1000	1,0/1,6	1100	2100	1950	2350	1025/1400	3750	900
15	1125	1,0/1,6	1200	2150	1950	2400	1025/1400	3400/3650	1000
17	1275	1,0/1,6	1200	2300	1800	2700	1200/1400	3400/3650	1000
21	1600	1,0/1,6	1400	2400	2000	2750	1200/1400	3400/3650	1100

Please enquire for larger capacities in our passenger range and for a full technical consultation and alternative options.