

GO! Flex - Specification Table

	STANDARD	OPTIONAL
FEATURES		
TYPE	Gearless Traction	
LOAD	480kg to 1600kg	
CAPACITY	6 to 21 persons	
SPEED	1 m/s – 1.6m/s	Please enquire
SUSPENSION	2:1	
TRAVEL RANGE	Up to 48 meters	Please enquire
STOPS	16 stops	Please enquire
ENTRANCES	Single Entrance	Double entrance 180 °
SERIES	"S" Machine room less	
CAR		
MODEL	VILITER RANGE	See full range of options in our Car finishes section
WALL FINISH	Plastic Coated steel - Choice of 5 colours	See full range of options in our Car finishes section
FLOOR FINISH	Circle Rubber – Choice of 3 colours	See full range of options in our Car finishes section
SKIRTING	Aluminium	Black
MIRROR	Panel width at rear of car	See full range of options in our Car finishes section
HANDRAILS	1 Handrail at rear of car – Steel finish	See full range of options in our Car finishes section
HEIGHT	2100mm	Please enquire
EXTERIOR DIMENSIONS	See Technical table	Please enquire
CEILING	Black painted steel with LED downlighters	See full range of options in our Car finishes section
CAR DOORS		
TYPE	Automatic: 2 side opening panels 3VF	Automatic: Centre opening
FINISH	Primer	Stainless Steel
DIMENSIONS	See technical table x 2000mm	Other heights available please enquire
SILLS	Aluminium	
LANDING DOORS		
TYPE	Automatic: 2 side opening panels 3VF	Automatic: Centre opening
FINISH	Primer	Stainless Steel
DIMENSIONS	See table x 2000mm	Other heights available please enquire
FIRE RATING (EN81-51)	E 120 EW 60	Please enquire
SILLS	Aluminium	
SHAFT		
DIMENSIONS	See Technical Table	
PIT	See Technical Table	
HEADROOM	See Technical Table	
CAR OPERATING PANEL		
MODEL	Full Height Control Station	Please enquire
FINISH	Stainless Steel X02 with Black Frame	See full range of options in our Car finishes section
PUSHBUTTONS	Impulse Model – tactile buttons with font plate in black anodised stainless steel – with blue or white lighting	Style Pushbuttons – please enquire
CAR INDICATORS	EMT3 LCD display	TFT – high resolution graphic indicator with multi-coding interfaces
SAFETY	Emergency Light and telephone	
LANDING OPERATING PANEL AND LANDING DISPLAY		
MODEL	Single pushbutton in door frame	Pushbutton panel with EMT3 display or TFT Display
FINISH	Stainless Steel Plate (X02)	Please enquire
PUSHBUTTONS	Impulse – font plate in black anodised stainless steel – with blue or white lighting	Style Pushbuttons
LANDING DISPLAY	Direction arrows in Door Jamb	
CONTROLLER		
TYPE	Via Series Controller - down collective	Full collective
LOCATION	Cabinet on the top floor – primer finish	Can be positioned on any floor also with a stainless steel finish
MACHINE		
	Gearless, permanent maGO magnets with thermal safety cover for motor.	
ELECTRICAL FEATURES		
VOLTAGE	380 to 415 V three phase	
LIGHTING VOLTAGE	220V	
FREQUENCY	50 Hz	
OPTIONAL EXTRAS		
	Please contact	