

Moving Walkway - Specification Table

	COMMERCIAL RETAIL INCLINED MOVING WALKWAY		PUBLIC SERVICE MOVING WALKWAY		HORIZONTAL MOVING WALKWAY	
INSTALLATION	Indoor/Outdoor Commercial*		Indoor/Outdoor Heavy Duty*		Indoor/Outdoor Heavy Duty*	
WORKING HOURS (hours per day)	16		16		16	
SLOPE ° (degrees)	10°,11°,12°		10°,11°,12°		0° - 6°	
SPEED (m/s)	.5m m/s		.5 m/s		.5 m/s	
CAPACITY (persons per hour)	Up to 6000		Up to 6000		Up to 6000	
WIDTH OF TREAD(mm)	800/1000		800/1000		1000,1200,1400	
DIFFERENCE IN HEIGHT	2.0 m to 7.5m		2.0 m to 7.5m		L 20 to 120m	
FINISHES	Standard	Optional	Standard	Optional	Standard	Optional
Balustrade Panel	10mm Safety Glass	Hairline Stainless Steel	10mm Safety Glass	Hairline Stainless Steel	10mm Safety Glass	Hairline Stainless Steel
Cladding	Primer Coated	Stainless Steel	Primer Coated	Stainless Steel	Primer Coated	Stainless Steel
Step Colour	Aluminium	Any colour	Aluminium	Any colour	Aluminium	Any colour
Handrail Colour	Black	Any colour	Black	Any colour	Black	Any colour
STANDARD FEATURES						
Handrail speed monitor	✓		✓		✓	
LCD Display Controller	✓		✓		✓	
Emergency pushbuttons	✓		✓		✓	
Yellow step outline	✓		✓		✓	
Traffic Lights	✓		✓		✓	
Fire alarm contact	✓		✓		✓	
Motor overheat protection	✓		✓		✓	
Landing plate contacts	✓		✓		✓	
Step missing contact	✓		✓		✓	
Anti-climb device	✓		✓		✓	
Triangle protection	✓		✓		✓	
Rated/Low speed – Power saving	✓		✓		✓	
Comb Lighting	✓		✓		✓	
Steel skirt covered by transparent teflon	✓		✓		✓	
Skirting brush	✓		✓		✓	
Auto Lubrication system	✓		✓		✓	
OPTIONAL FEATURES						
Skirting Board Lighting	✓		✓		✓	
Balustrade Lighting	✓		✓		✓	
Comb Heating	✓		✓		✓	
Truss Heating	✓		✓		✓	
*Outdoor Electrical installation to include for anti-rust nuts and screws, Oil water separator, flooding of shaft.	✓		✓		✓	
Pit Float Contact (Outdoor Unit)	✓		✓		✓	
	✓		✓		✓	

NOTE: Please enquire for a full technical consultation