

Parking Lifts - Specification Table

	STANDARD	OPTIONAL
FEATURES		
TYPE	Hydraulic lift	
LOAD	3000kg to 6500kg	
SPEED	.4m/s and .5m/s	.5m/s
SUSPENSION	1:1 and 2:1	
TRAVEL RANGE	Up to 12 meters	Please enquire
STOPS	5 stops	Please enquire
ENTRANCES	2 Entrances – Through Car	
SERIES	‘C’ with a machine room	
CAR		
MODEL	FORTE-CAR	
WALL FINISH	Grey powder coated steel	Stainless steel or galvanised plate
FLOOR FINISH	Painted steel checker plate (RAL 7044)	Aluminium checker plate or stainless steel checker plate
SKIRTING	Painted Steel	Stainless Steel
PROTECTION BANDS/BUMPERS	Plained and varnished Timber	Rubber, Galvanised or stainless steel
CEILING	Flush diffused lighting	Please enquire
HEIGHT	2180mm	Please enquire
EXTERIOR DIMENSIONS	See Technical table	
CAR DOORS		
TYPE	Automatic 4 or 6 centre-opening panels 3VF	
FINISH	Primer	Stainless Steel
DIMENSIONS	See table x 2000m	Other heights available
SILLS	Reinforced Aluminium	Stainless Steel, Massive Iron
LANDING DOORS		
TYPE	Automatic 4 or 6 centre-opening panels	
FINISH	Primer	Stainless Steel
DIMENSIONS	See table x 2000mm	Other heights available please enquire
FIRE RATING	E 120 (EN81-58)	Please enquire
SILLS	Reinforced Aluminium	Stainless Steel, Massive Iron
SHAFT		
DIMENSIONS	See Table	
PIT	See Table	
HEADROOM	See Table	
CAR OPERATING PANEL		
MODEL	Full Height Control Stations x 2 assembled diagonally which allow vehicles to enter the car in both directions.	Please enquire
FINISH	Stainless Steel X02	Please enquire
PUSHBUTTONS	According to EN8170	Vandal Proof
CAR INDICATORS	EMT3 LCD display	TFT – high resolution graphic indicator with multi-coding interfaces
SAFETY	Emergency Light and telephone	
LANDING OPERATING PANEL		
MODEL	Single pushbutton in door frame	Please enquire
FINISH	Stainless Steel Plate (X02)	Please enquire
PUSHBUTTONS	Impulse – font plate in black anodised stainless steel – with blue or white lighting	Please enquire
ENGRAVING	Laser	
CONTROLLER		
TYPE	Microprocessor controller – down collective or	Via series
LOCATION	In the machine room	
POWER UNIT		
	Motor manometer-theristor thermal contact for oil	
	Electromechanical valve block	
	Manual pump – oil	Oil cooler
	Automatic rescue	Electronic valves
ELECTRICAL FEATURES		
VOLTAGE	380 V three phase	
LIGHTING VOLTAGE	220V	
FREQUENCY	50 Hz	60Hz
ADDITIONAL FEATURES		
LANDING CONTROL STATION WITH KEYSWITCH	All landing pushbuttons are keys which record calls from authorised persons	
INTERCOM	Allows communication from the outside terminal at all times	
TRAFFIC LIGHTS	Allowing for smoother traffic flow	
OPTIONAL EXTRAS		
REMOTE CONTROLS	No need to get out of vehicle to call the lift	