

Strongo - Technical Table

Capacity		Speed (m/s)	Car dimensions (mm) Height 2100 mm			Shaft dimensions (mm)			Clearance (mm)
People	Load (Kg)		Clear Ope	Width	Depth	Width	Depth	Pit	
17	1275	1,0/ 1,6	(T2) 1000	1200	2300	1750	2550	1200	3400/3600
20	1500	1,0 /1,6	(T2) 1000	1900	1750	2600	2300	1200/1500	3700/3800
21	1600	1,0 /1,6	(T2) 1100	1600	2200	2200	2800	1400/1500	3700/3800
26	2000	1,0 /1,6	(C4) 1400	2000	2100	2950	2400	1400/1500	4050
33	2500	1,0 /1,6	(C4) 1400	2000	2500	2950	2800	1400/1500	4250
40	3000	1,0	(C4) 1400	1850	3000	3150	3300	1600	4100
46	3500	1,0	(C4) 1800	2000	3200	3300	3500	1600	4100
53	4000	1,0	(C4) 1800	2100	3400	3400	3700	1600	4100
60	4500	1,0	(C4) 1800	2250	3500	3750	3850	1600	4100
66	5000	1,0	(C4) 1800	2500	3500	4000	3850	1600	4100
73	5500	0,5	(C4) 1800	2500	3800	4000	4150	1600	4100
80	6000	0,5	(C4) 1800	2600	4000	4100	4350	1600	4100
86	6500	0,5	(C4) 1800	2600	4300	4100	4650	1600	4500

NOTE 1: The shaft dimensions given in the table are the minimum required in accordance with EN81-1/2 standard. Our flexibility allows us to adapt to reduced dimensions. Please enquire for further details.

NOTE 2: The table shows the minimum measurements.