



ILS 05K take flexibility to a new level.

ILS 05K is by the first look a normal platform lift, even if we are really proud of the design. What differs us from others is our innovative solutions, and just to mention some things this give:

- ◆ Several different platform sizes to choose from and a shaft pit of only 50mm, this means that we always have a lift that fits your building.
- ◆ Small lift dimensions which means that you always have the space for **ILS 05K**.
- ◆ 500 kg free of charge.
- ◆ Soft start/stop as standard for best comfort.
- ◆ A fantastic design and construction for an easy and quick installation, plug n´ play all the way through.
- ◆ Competitive material prices and short installation times, do that **ILS 05K** probably have the best price on the market.

Thanks to our great design, our construction and our flexibility, **ILS 05K** fits into all environments, both public and private, and just to mention some examples: shops, care homes, arenas, schools, offices, or why not at home in you private house, yes, everywhere where design, surface and economy is a demand.

ILS 05K always have 1000mm wide and fully glazed doors as standard when you choose a platform that is 1100mm wide. As an option you can of course choose fire rated EI60 doors. All our pushbuttons have both tactile and braille.

Other possible options: phones, different choices of flooring, locking, voice announcement, automatic door openers, level indicators, arrival bell, glazed shaft panels, lift painted in other RAL colours, elbow buttons, or why not have some parts in brushed stainless steel. Just to mention some options.

A lift from **Innovation Lift Scandinavia AB** gives you an easy and smooth life, and we are convinced that you will not regret your choice of lift.

Recommended installation	Indoors
Rated load	500 kg
Rated Speed	max 0,15 m/sec
Height limits	max travel height 13m top Height 2,3 m / 1,1m
Pit depth	50 mm (ramp 50mm optional)
Stops	5 stops
Standard platform sizes (w x d)	1000 x 1500 / 1100 x 1500 / 1100 x 1600
Standard lift dimensions (w x d)	1370 x 1580 / 1470 x 1580 / 1470 x 1680 *, **
Cut-out size	+ 30 mm on above
Other platform dimensions width	700 – 1100
Lift dimension (w)	+ 370 mm (+400 mm if door on B-side)
Other platform dimensions depth	1100 – 1600
Lift dimension (d)	+ 80 mm (if door on A & C +110mm)
Cut-out size	+ 30mm
Standard Shaft finish	Laminated sandwich panels in RAL 9003 (white) (T=25mm, H=565mm), Glazed panels optional.
Standard platform finish	RAL 9003 (white) All powder coated, other RAL colours available upon request, black rubber flooring.
Doors	Swing doors, doors can be on 3 sides
Drive system	Screw and nut
Control system	PLC
Power supply	380-400V 3-phase 50/60 Hz 16A, 230V 3-phase 50/60 Hz 16A frequency converter as standard *230V 1-phase 50/60 Hz 16A with frequency converter optional
Motor	2,2 kW
Battery emergency lowering	incl. as standard
Door buttons	one touch
Platform buttons	Hold to run All buttons with tactile and braille
Certification	MD 2006 / 42 / EC, EN81-41
Manufactured in	Sweden

* If door on side A & C=+30mm

** If door on side B, w=+30mm

